



### HC-WPB-40W

Watts	40W
Lumens	5200lumens
LED type	SMD3030
Bean Angle	140°
CRI	>80
Packing	weight:8kgs/pcs
	Size:405*290*255mm/carton
Replace Watt	150W-250 HID



### Hc-wpb-60w

Watts	60W
Lumens	7800lumens
LED type	SMD3030
Bean Angle	140°
CRI	>80
Packing	weight:8kgs/pcs
	Size:405*290*255mm/carton
Replae Watt	250W-400W HID



### Features>>

- 100-277V UL/cUL driver & 100-240V meanwell driver
- ETL cETL DLC approved
- Best quality with 5-Years Warranty
- Protective powder coating for lasting appearance
- IP65 rating for outdoor use
- Integrated thermal management system
- Bronze housing and Black housing is optional
- OEM: Metal Label of Logo available
- ◆ Working Temperature is -30°~+40°; Storage Temperature is -40°~+80°
- Material:Aluminum+Glass cover (Plastic cover is optional)



## Certification >>












## Hc-wpb-100w

Watts	100W
Lumens	12000lumens
LED type	SMD3030
Bean Angle	140°
CRI	>80
Packing	Weight:12kgs/pcs
	Size:530*290*300mm/carton
Replace Watt	600W HID



### **DLC** premium>>

#### First Generation

Watts 36W/60W/90W 80lumens/W Lumens LED type SMD5630 Installation Need to open light Fan

No Fan DLC DLC standard

#### **New Generation**

40W/60W/100W Watts Lumens 120lumens/W LED type

Installation No need to open light, install easily to save labor cost Fan With SUNON fan for 60W/100W


DLC **DLC** premium

# **DLC** premium >>



## Hc-wpc-40w


Watts	40W
Lumens	5200lumens
LED type	SMD3030
Bean Angle	140°
CRI	>80
Carton Size	405*285*345mm
Replace Watt	150W-250 HID





## Hc-wpc-60w

Watts	60W
Lumens	6000lumens
LED type	SMD3030
Bean Angle	140°
CRI	>80
Carton Size	405*285*345mm
Replace Watt	250W-400W HID






## Hc-wpc-100w

Watts	100W
Lumens	10000lumens
LED type	SMD3030
Bean Angle	140°
CRI	>80
Carton Size	505*290*410mm
Replace Watt	600W HID









### Features>>

- 100-277V UL/cUL driver & 100-240V meanwell driver/347-480VAC
- ETL cETL DLC approval;
- Best quality with 5-Years Warranty
- Protective powder coating for lasting appearance
- ◆ IP65 rating for outdoor use
- Integrated thermal management system, SUNON fan (60W/100W)
- Bronze / Black housing
- Working Temperature is -30°~+40°; Storage Temperature is -25°~+60°
- Material:Aluminum+Glass cover (Plastic cover is optional)



## Certification >>









